

# PRODUCT DATA SHEET



## RENOTUB™ 2K BATH ENAMEL PAINT

---

Renotub is a durable two-part modified acrylic isocyanate free coating specially formulated and designed to provide excellent adhesion, durability and colour retention in high moisture areas. It is ideal for use to renew cast iron, steel, enamel, ceramic porcelain, fiberglass, acrylic, bath tubs, toilets, bidets and sinks. It is not for use on galvanized steel or flexible plastic.

Do not use on areas exposed to extreme heat such as stovetops, or constant high humidity environments. Do not use in continuous water immersion such as swimming pools, hot tubs, ponds, or saunas.

Because of its special properties Renotub is undoubtedly one of the best resurfacing and tile painting products on the market. Ideal for brush and roller application.

With Renotub you can transform your entire bathroom suite for relatively little expense and time!

Our proven formula works on worn, discoloured or badly stained surfaces – saving you hundreds of pounds on the cost of replacement.

Renotub has a glossy finish with good gloss retention.

1:1 mixing ratio for easy use and reduced wastage. Specially designed for application with brush and roller.

Each pack contains a 250ml of Part A coating in Brilliant White Ral 9016 and 250ml Part B of an Activator / Hardener.

### Usage

Before applying carefully read the instructions on the container and use according to the manufacturer's recommendations.

### Preparation

To secure lasting adhesion to the subsequent product all surfaces shall be clean, dry and free from any contamination.

Clean the surface in preparation for sanding.

Thoroughly abrade the surface with a suitable P600 abrasive sandpaper. Remove loose paint and rust with a wire brush.

To ensure a clean tidy finish round the edges and the fittings, we recommend applying masking tape to areas that do not require resurfacing and renovating.

## Application

Apply at temperatures between 10-25°C in a well ventilated room.

Before painting mix components A and B and stir thoroughly. Once mixed apply within 2 hours.

Use a fine quality, fine bristle brush. Brush in one direction only for a smooth surface and feather the edges as you paint to avoid a hard line between painted areas. Avoid excessive brushing to ensure an even coat and smooth finish. Brush around the edges and the fittings and when complete we recommend applying the surface with a good quality 4" foam roller.

Allow to dry 7 days before exposing to water.

<b>Substrate temperature</b>	<b>20°C</b>
Surface (touch) dry	2 Hours
Hard Dry	24 Hours
Minimum Overcoating	4 Hours
Full Cure	Allow 7 Days

Surface (touch) dry: The state of drying when slight pressure with a finger does not leave an imprint or reveal tackiness.

## Coverage

8m<sup>2</sup> per 500ml pack

## Colour

Brilliant White Ral 9016

## Storage and Shelf Life

Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 20°C - 48 months

Flash Point - 82 °F (28 °C)

Volatile Organic Compounds (VOC) – 387g/l



## Health and Safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.