

PRODUCT DATA SHEET



RENOTUB™ PREMIUM MOULD RESISTANT PAINT

Renotub™ Premium Mould Resistant Paint has been formulated for use in high risk areas where humidity and decorative, superior emulsion for combating internal problems of mould growth.

It provides long-term protection from mould and algae and is designed to stop further contamination and discolouration.

Renotub™ Premium Mould Resistant Paint is economic and easy to apply, providing a long lasting durable scrubbable finish.

Ideal for:

- Bathrooms
- Ensuites and shower rooms
- Kitchens
- Laundry rooms
- Utility Rooms
- Basements
- Garages
- Areas of high humidity

Use for use as a biocidal paint.

Usage

Before applying carefully read the instructions on the container and use according to the manufacturers recommendations and instructions.

Preparation

Where mould is present:

- 1). Wash area with a professional, good quality mould remover.
- 2) Allow 1 hour to dry and wash down with warm water.
- 3) Ensure sound surface before using Renotub™ Premium Ant-Mould Paint.

Application

Apply at temperatures between 10-25°C in a well ventilated room.

Apply by brush and roller.

The first coat may be thinned by up to 10% maximum with clean water.

Do not thin the second coat. Stir well before use.

Drying Time - 2 Hours

Minimum Overcoating Time - 4 Hours

Coverage

Up to 10-12m² per 1 litre. Coverage may vary depending upon application method and rate of application.

Colour

Brilliant White

Storage and Shelf Life

The product must be stored in accordance with national regulations.

Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

Containers must be kept tightly closed. Handle with care.

Store Safely above 5°C.

Protect from frost. Shelf life 24 months @ 20 degree.

This product contains minimul VOC content 0-0.29%.

Paint Product UN1263

Contains: A mixture of 5-Chloro-2-Methyl-2H-Isotiazol-3-One [EC No 247-500-7]